

# Fairing Compound

23 September 2015 DATA SHEET V2

## Description:

A dark grey cement based internal slurry plaster. Can be applied with a trowel, sponge or block brush.

## General Uses:

Fairing compound is used for repairing/making good defective plaster work.  
It requires only the addition of water to achieve a fine ready-to-use slurry base.  
Develops a hard, durable smooth surface ready for further coating or finishing.  
Allow 24 hours for hardening.



## Application:

Repair walls where defective plastering has resulted in uneven finish. Always use bonding liquid as additive.

## Additional Information:

Do not add any foreign matter into the mix (gypsum, lime, cement, etc.)  
Clean tools immediately after use with water.  
Do not mix or apply product in temperatures above 35 deg C or below 5 deg C.

## Technical Information

### PROPERTIES

Water  
Workability & consistency  
Pot life of mix  
Setting time  
Tensile adhesion strength  
Flexural strength  
Compressive strength  
Water absorption  
Shrinkage  
Product packaging

### RESULTS

As required  
Good  
100 minutes  
360 minutes  
0.674 n/mm<sup>2</sup>  
4.30 n/mm<sup>2</sup>  
13 – 80 n/mm<sup>2</sup>  
2.19 kg/m<sup>2</sup>H  
3.73 mm/m  
25kg bag