

Skimfill Interior

23 September 2015 DATA SHEET V2

Description:

A white cement based skimming compound to be applied on internally plastered walls before final decoration. Develops a durable surface with high scratch-resistance. No bonding liquid required, even on painted surfaces. Skims over and fills cracks easily and can be over-painted after 24 hours.

RECOMMENDED FOR:

- INTERIOR surfaces.
Used as a hairline crack filler, or as a scraper coat over cement plaster (eliminating the need for filling).
Also suitable for skimming over defects in plasterwork, for skimming after alterations or renovations to marry new and old surfaces, and for skimming over correctly prepared pre-painted surfaces to provide an even surface.

NOT RECOMMENDED FOR:

- Not suitable for exterior use or for cracks >0.5mm.



APPLICATION AND SPREAD RATES:

Apply using a steel trowel or spackle tool. Sand when dry +/- 4 hours after application depending on thickness. 100 grit or finer sandpaper is recommended.

SPREAD RATES

On reasonable plaster +/- 3.4m²/kg as a scraper coat.

TECHNICAL DATA			
Properties	Results	Properties	Results
Water demand	26.5%	Drying time	±35 mins
Workability & consistency	Good	Tensile adhesion strength	0.64N/mm ²
pH	10.50 – 11.00	Flexural strength	4.30 N/mm ²
Pot life of mix	100 minutes	Compressive strength	13.80 N/mm ²
Water absorption	2.19 kg/m ² .h	Shrinkage	3.73 mm/m
Product packaging	20kg		